

H-400A/GA 全自動油壓龍門式帶鋸機

DOUBLE COLUMN HEAVY DUTY AUTOMATIC HORIZONTAL BANDSAW



規格表 Specifications

規格 / 機型 SPEC. / MODEL	H-400A/GA	
鋸切能力 Cutting Capacity	mm	● 400 ■ 400W X 400H
	in	● 16 ■ 16W X 16H
整把切削 Bundle Cutting	mm	320W X 230H
	in	12.6W X 9H
鋸帶尺寸 Blade Size	mm	34W X 1.1t X 4570L
	in	1.34W X 0.042t X 179.92L
鋸帶速度 Blade Speed	M/min	25,32,42,55,70,80 無段變速 Variable Speed20-80(選配 Opt.)
	F/min	82,105,138,180,230,260 無段變速 Variable Speed65-260(選配 Opt.)
馬達 Motor Output	HP	鋸帶 Blade5 , 油壓 Hyd.1 , 冷卻 Coolant 1 / 8
	KW	鋸帶 Blade 3.75 , 油壓 Hyd 0.75 , 冷卻 Coolant 0.1
封箱尺寸 (L X W X H) Shipping Volume	mm	2520 X 2070 X 2000
	ft	8.27 X 6.79 X 6.56
淨重 / 毛重 N.W. / G.W.	kg	2100 / 2320
	lb	4620 / 5100

標準配備 Standard Equipment

工具箱 Tools with tool box	1 只 set
2M(7 ft.)長滾輪台 Long roller table with vertical roller guides	1 台 set
清屑鋼刷輪 Band-cleaning wire brush	1 件 pc
鋸帶 Bandsaw blade	1 條 pc
油壓張力 Hydraulic blade tension	1 組 set
自動清屑裝置 Automatic chip conveyor	1 組 set
操作手冊與零件清單 Instruction manual and parts list	1 本 copy

選擇配備 Optional Equipment

- 鋸速無段變速 Variable blade speed drive.
- 夾鉗壓力可調 Variable vise pressure system.
- 鋸切速率調整用增幅閥
Amplifying valve for auto-adjusting cutting feed-rate.
- GA 型切削長度電腦數值控制 GA Numeric control.
- 深度切削 Cutting depth control.